



Technical Data Bulletin

501 S. Water St. • Stoughton, WI 53589
 Customer Service: 800-873-8800
 Sales: 888-646-2542

PATTERN: "BOURBON STREET" Revised 09/01
 88 (SPS-0196)

DESCRIPTION: Expanded vinyl on Jersey Knit.
 Advanced "BeautyGard" protective finish.
 Micro-perforated for breathability

<u>MATERIAL CHARACTERISTICS:</u>	<u>REQUIREMENTS</u>			<u>TEST</u>
	STD	MIN	MAX	<u>METHOD</u>
Width, inches		54		191A-5020
Weight, oz/yd ²	18.8	17.5	20.1	191A-5041
Thickness, mils	45	40	50	CS-273-65
Coating/Fabric Bond lb./in				
Machine Direction		3.0		CFFA-3A
Cross Direction		3.0		CFFA-3A
Tensile Strength, lb.				
Machine Direction		40		CFFA-17
Cross Direction		40		CFFA-17
Tearing Resistance, lb.				
(Trapezoid Method)				
Machine Direction		12		CFFA-16C
Cross Direction		12		CFFA-16C

(continued)

"ALL RECOMMENDATIONS FOR THE USE OF THE PRODUCT OR PRODUCTS DESCRIBED HEREIN AND ALL OTHER DATA OR INFORMATION SET FORTH IN THIS BULLETIN, WHETHER CONCERNING SUCH PRODUCTS OR OTHERWISE, ARE FURNISHED WITHOUT ANY GUARANTEE, WARRANTY, REPRESENTATION OR INDUCEMENT OF ANY KIND. WHETHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND UNIROYAL EXPRESSLY DISCLAIMS LIABILITY UNDER ANY THEORY INCLUDING, WITHOUT LIMITATION, CONTRACT NEGLIGENCE, MISREPRESENTATION OR BREACH OF ANY OBLIGATION RELATING TO THE RECOMMENDATION, DATA OR INFORMATION SET FORTH HEREIN, READERS AND CUSTOMERS ARE ENCOURAGED TO CONDUCT THEIR OWN TESTS, READ ALL LABELS AND INSTRUCTIONS BEFORE USING ANY PRODUCTS."

WHERE FLAME, SMOKE, FIRE, CODES, ETC. ARE INDICATED THE FOLLOWING APPLIES:
 "THIS TERM AND ANY CORRESPONDING DATA REFER TO TYPICAL PERFORMANCE IN THE SPECIFIC TESTS INDICATED AND SHOULD NOT BE CONSTRUED TO IMPLY THE BEHAVIOR OF THIS OR ANY OTHER MATERIAL UNDER OTHER FIRE CONDITIONS."

TECHNICAL DATA BULLETIN

Revised 09/01
(SPS-0196)

"BOURBON STREET"
(BB)

<u>MATERIAL CHARACTERISTICS:</u>	REQUIREMENTS	TEST METHOD
Abrasion Resistance	4100 cycles with 2.5# tension, 3.5# load, 320-E 9/0 sandpaper. Shall not wear through the solid film layer.	CFFA-1a Wyzenbeek
	No wear through solid film layer at 250,000 double-rubs with #8 cotton duck.	CFFA-1a Wyzenbeek
Blocking	No. 3 rating maximum.	CFFA-4
Crocking	No appreciable discoloration of the cloth patch.	CFFA-7A
Low temperature Resistance	No cracking at -20 degrees Fahrenheit	191A-5874 5# roller
Accelerated weathering Resistance	No appreciable discoloration fading or stiffness after 138hours	ASTM G-23 Weatherometer
Accelerated Ultraviolet Exposure Resistance	No appreciable discoloration fading or stiffness after 120 hours.	ASTM G-25 Fadeometer
Breathability	One cubic foot per minute minimum air flow rate on 10" circular specimen. (5" water column pressure, approx. 0.2 psi)	PTI#508 UEP tester

BOURBON STREET is formulated to meet the small scale flammability test requirements for upholstered materials contained in the following specifications:

Motor Vehicle Safety Standard No. 302
California Technical Bulletin 117-2013
BIFMA, Screen Test 4.6.1.1

Test Method Codes: "191A" -Federal Test Method Standard 191A
Textile Test Methods
"CFFA" -Chemical Fabrics and Film Assn.
"CS" -Commercial Standard, Dept. of Commerce