



Received: 07/12/2018 Completed: 07/23/2018 Letter: H2 BG P.O.#: 4500027812 Test Report #: 3-27317-0-02

Client's Identification Item: 1015-06181. SPS-0152. Date of Mfg.: 6/28/18. Product End Use: Upholstery.

Tested For: **Kristi Rygh** Key Test: NFPA 260 Cover Fabric (BLDG) 235  
 Uniroyal Engineered Products, LLC  
 501 South Water Street  
 Stoughton, WI 53589  
 Tel: 1-(608)-873-6631 Ext:  
 Fax: 1-( )- -

Category: NFPA 260 Fabric LE 2013; V 04/18 PC: 4H NTR 4/16 dl/jd SM/mg  
 NFPA 101 LE 2015; V 04/15  
 IFC LE 2015; V 03/15

TEST PERFORMED: NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture; Cover Fabric Test

Ignition Source: SRM 1196 Cigarette

SPECIMEN TEST COMPOSITE:

Candidate Cover Fabric: See "Client's Identification"  
 Standard Filling Material: Non FR polyurethane foam, density 20 kg/m<sup>3</sup> to 25 kg/m<sup>3</sup>

| RESULTS:   | TEST                 | RETEST (If Required)               |                                    |
|------------|----------------------|------------------------------------|------------------------------------|
| Specimen # | Ignition (yes/no/SE) | Char Length on Vertical Panel (mm) | Char Length on Vertical Panel (mm) |
| 1          | SE                   | 0                                  | 0                                  |
| 2          | SE                   | 0                                  | 0                                  |
| 3          | SE                   | 0                                  | 0                                  |

ABBREVIATION WHICH MAY BE USED:

SE = Indicates that the cigarette self extinguished prior to burning its entire length. When this occurs, a "retest" of that specimen is performed.

EC = Escalating combustion. Specimen extinguished by technician. No char length measurement taken.

CLASSIFICATION SYSTEM:

Class I - For each specimen: No obvious ignition; maximum char length 45 mm (1.75"). (Indicates propensity to resist cigarette ignition in conjunction with standard foam filling material.)

Class II - For any specimen: Obvious ignition; or char length exceeding 45 mm (1.75"). (Indicates inability to resist cigarette ignition in conjunction with standard foam filling material.)

|                             |                              |                   |    |                          |                                    |
|-----------------------------|------------------------------|-------------------|----|--------------------------|------------------------------------|
| <b>Received:</b> 07/12/2018 | <b>Completed:</b> 07/23/2018 | <b>Letter:</b> H2 | BG | <b>P.O.#:</b> 4500027812 | <b>Test Report #:</b> 3-27317-0-02 |
|-----------------------------|------------------------------|-------------------|----|--------------------------|------------------------------------|

**Client's Identification** | Item: 1015-06181. SPS-0152. Date of Mfg.: 6/28/18. Product End Use: Upholstery.

**Tested For: Kristi Rygh** **Key Test: NFPA 260 Cover Fabric (BLDG)** 235  
 Uniroyal Engineered Products, LLC  
 501 South Water Street  
 Stoughton, WI 53589 **Tel:** 1-(608)-873-6631 **Ext:**  
**Fax:** 1-( )- -

CONCLUSION: Based on the reported Results and cited Classification System, the item tested is assigned a:

Class I rating;  Class II rating

REMARKS: None.

CODE INFORMATION:


- (1) The 2015 Edition of the NFPA Life Safety Code 101, paragraph 10.3.2.1(1); and
- (2) The 2015 Edition of the International Fire Code, paragraph 805.1.1.1, 805.2.1.1, 805.3.1.1, and 805.4.1.1

Upholstered furniture components shall be Class I when tested in accordance with NFPA 260 when specified by certain occupancies (provided that they are sprinklered throughout). The typical occupancies are:

- Healthcare
- Lodging & Rooming Houses
- Hotels
- Dormitories
- Residential Board & Care

NOTE: Non-sprinklered occupancies may require ASTM E1537.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.



Phyllis Pettit

AUG 02 2018

-----  
 AUTHORIZED SIGNATURE  
 SGS GOVMARK  
 / jab