



Safety Data Sheet

Issue Date: 1/2017

Section I - Chemical Product and Company Identification

Uniroyal Engineered Products
501 S. Water Street
Stoughton, WI 53589

Phone (608) 873-6631

Naugahyde Brand Vinyl Coated Fabrics and Vinyl Roll Goods

Section II - Hazardous Ingredients

These products are considered manufactured articles per OSHA Hazard Communication Standard 29CFR 1910.1200. All hazardous components present are bound in the polymer, and no exposure to these components occurs during normal use.

Section III - Composition

Compounded Polyvinyl Chloride plastic film or foam; may be laminated to textile fabric which sometimes includes polyurethane foam.

Section IV - First Aid Measures

No hazard is expected under normal conditions of use. Processing above 175°F may produce pulmonary irritants requiring ventilation. In the event of high heat due to fire, remove victims to fresh air, and call physician immediately.

NAUGAHYDE
BRAND FABRIC



Section V - Fire Fighting Measures

Water, carbon dioxide, foam or dry compounds can be used. Use self-contained breathing apparatus as combustion products are toxic. Combustion products include hydrogen chloride, a pulmonary irritant.

Section VI - Accidental Release Measures

No special steps are necessary if material is released or spilled.

The material may be buried in approved landfill sites if authorized by federal, state, and local laws. These materials are not a hazardous waste as defined by the Resource Conservation and Recovery Act.

Section VII - Storage and Handling

Store in a cool, dry place.

If processing above 175°F, use local ventilation, safety glasses, and gloves.

Section VIII - Exposure Controls and Personal Protection

None are necessary under normal environmental conditions.

If processing above 175°F, use local ventilation, safety glasses, and gloves.

Section IX - Physical and Chemical Properties

Boiling Point: NA* Specific Gravity: Approx. 0.7 Vapor Pressure: NA*

Percent Volatile, by Volume: Essentially Non-Volatile Evaporation Rate: NA*

Solubility in Water: Negligible Appearance and Odor: Solid Material in sheet form with mild odor.

NAUGAHYDE
BRAND FABRIC



Section X - Stability and Reactivity

Stability: Stable **Conditions to Avoid:** Heating above 175°F without ventilation.

Materials to Avoid: None Known **Hazardous Polymerization:** will not occur

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide, Hydrogen Chloride and various organic compounds.

*-Not Applicable

Section XI - Toxicological Information

Not defined as a hazardous material. See Section III

Section XII - Ecological Information

These materials can be buried in approved land fill sites if authorized by federal, state and local laws. These products are not a hazardous waste as defined by the Resource Conservation and Recovery Act. No impact on the environment is known.

Section XIII - Disposal Considerations

These materials can be buried in approved land fill sites if authorized by federal, state and local laws. Certain material of this type can be recycled.

Section XIV - Transportation Information

No special shipping or labeling is required.

NAUGAHYDE
BRAND FABRIC



Section XV - Regulatory Information

The material does not fall under any special regulatory guidelines.

Section XVI - Other Information

Prepared By Uniroyal Engineered Products' Research Laboratory.

NAUGAHYDE
— BRAND FABRIC